

CardMan® 6121 Dongle

OMNIKEY, one of the world leading manufacturers of innovative smart card readers, has developed a new portable USB smart card reader. The CardMan® 6121 is a fully functional smart card reader for SIM-sized smart cards and is especially well suited for the use with mobile devices.



High-Speed

Based on revolutionary chip technology, jointly developed with Atmel, the portable CardMan® 6121 supports reader-to-card data transmission rates of up to 420 KBits per second, exceeding the performance of other smart card readers.

Standards

Because the CardMan® 6121 complies with all relevant industry standards (ISO 7816, EMV [Europay, Mastercard, Visa] 2000, Microsoft® WHQL, USB CCID, PC/SC, HBCI [Home Banking Computer Interface, the PC-2001 Specification and many more] it is open for any smart card on any computer for any application.

Applications

Applications for the new reader include the download of GSM applications from the internet to the SIM card, W-LAN authentication, secure PC log-on, PKI for mobile users, digital signature, secure mobile banking and online transactions, loyalty programs, healthcare solutions and many more future applications.

The usage within an application is based on standardized interfaces like PC/SC, OCF (Open Card Framework) or CT-API.

The 6121 is CCID-compliant and features a full-speed USB 2.0 interface. With CCID drivers becoming a standard feature of many operating systems, the 6121 can simply be plugged into a USB port and automatically be operated without the necessity to install additional drivers..



CardMan® 6121 Dongle

Host Interface	
USB 2.0 CCID ¹ [also compliant with USB 1.1]	✓
Transmission Speed	12 Mbps
Power supply	Bus powered
Smart Card Interface	
Compliant with ISO 7816 and EMV ² 2000 Level 1	✓
Supports T=0, T=1	✓
Supports 2-wire (SLE 4432/42), 3-wire (SLE 4418/28), SLE 4404	✓
Supports I ² C (S=8)	✓
Card Size	ID-000 (SIM size)
High performance smart card interface (up to 420 Kbps when supported by card)	✓
Smart card clock frequency up to 8 MHz	✓
Supports 5V, 3V & 1.8V smart cards	✓
Supplies 60 mA current to power the smart card	✓
Smart card movement detection with auto power-off	✓
Automatic detection of smart card type	✓
Short circuit and thermal protection	✓
Other Features	
Status indicator	LED
Options	
Customer specific logo or label	On request
Customer specific colors	On request

Compliance	
Microsoft® WHQL ³	✓
EMV ² 2000 level 1 certified	✓
ISO 7816	✓
HBCI ⁴	✓
USB 2.0 (USB 1.1 compatible)	✓
API	
PC/SC driver	✓
CT-API (on top of PC/SC)	✓
OCF (on top of [PC/SC])	✓
PC / SC Driver Support	
Windows® 98	✓
Windows® ME	✓
Windows® 2000	✓
Windows® XP	✓
Linux®	✓
Embedded Technology	
CardMan® Smart@Link Chip set	✓
Hardware Specifications	
Colors	Gray- Blue
Dimensions	74 x 21 x 10mm 2.34"x.70"x.30"
Weight	10 gr/0.35 ounces
Operating temperature	10-55°C/32-131°F
Operating humidity	10-90% rH
Composition	PC Lexan
Durability	100,000 Insertions
Meantime between failure	500,000 Hours
Safety and Environmental Standards	
CE	✓
FCC	✓
UL	Pending-March 2005

1= Chip Card Interface Device 2= Europay® MasterCard® Visa® 3= Windows® Hardware Quality Lab 4= Homebanking Computer Interface



info@omnikey.com
www.omnikey.com

OMNIKEY
Headquarters
Am Klingenberg 6 a
65396 Walluf, Germany
Tel: +49 6123 7913 0
Fax: +49 6123 7913 28

OMNIKEY
Americas
9294 Jeronimo Road
Irvine, CA 92618, USA
Tel: +1 949 598 1617
Fax: +1 949 598 5747

OMNIKEY
Asian Pacific
19 F King 's Road
North Point Hong Kong
Tel: +852 3160 4811
Fax: +852 8161 0070

For all other countries, please contact OMNIKEY headquarters.